

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 04-314795

(43)Date of publication of application : 05.11.1992

(51)Int.Cl.

C10M163/00  
 //(C10M163/00  
 C10M137:06  
 C10M133:44  
 C10M159:24  
 C10M125:10 )  
 (C10M163/00  
 C10M137:06  
 C10M133:44  
 C10M159:24  
 C10M125:10  
 C10M129:74 )  
 C10N 20:02  
 C10N 20:06  
 C10N 30:00  
 C10N 30:06  
 C10N 30:12  
 C10N 40:24

(21)Application number : 03-108818

(71)Applicant : SHOWA SHELL SEKIYU KK  
 KAWASAKI STEEL CORP

(22)Date of filing : 12.04.1991

(72)Inventor : IKAI TORU  
 NAGAYAMA SHINGO  
 HASHIMOTO HIROSHI  
 HIRA TAKAAKI

## (54) RUST-PREVENTIVE PRESS OIL

### (57)Abstract:

PURPOSE: To provide a rust-preventive press oil for surface-treated steel sheets which suffices when it is applied once on delivery as rust-preventive oil to a surface-treated steel sheet and excels in cleaning and degreasing performances in pretreatment before coating.

CONSTITUTION: A base oil is mixed with 1-5 pts.wt. pressability improving aid selected from the group consisting of alkali metal salts of alkyl acidic phosphates and alkaline earth metal salts of alkyl acidic phosphates, 0.01-1 pt.wt. oil stain preventive selected from the group consisting of an alkyl- benzotriazole and an arylbenzotriazole, 5-50 pts.wt. rust preventive selected from the group consisting of alkali metal salts of overbased alkylsulfonic acids and alkaline earth metal salts of overbased alkylsulfonic acids and 1-10 pts.wt. solid lubricant selected from the group consisting of alkali metal carbonates and oxides and alkaline earth metal carbonates and oxides mainly consisting of 1 $\mu$ m or smaller particles, and the viscosity (at 40° C) of the obtained mixture is adjusted to 5-40cSt.

## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than